

STRONG TRAILERS AT YOUR SERVICE

THE FUTURE IS BRIGHT !

BODY

The monocoque aluminium body is fitted on an alloy subframe. All aluminium plate in extra strong silica aluminium.

Sides:

- * Length inside: 13500 mm - outside: ± 14000 mm
- * Width inside: 2465 mm - Height inside: front: 2650 mm - back: 2825 mm
- * Coupling height : 1250 mm
- * Smooth panels (600 mm wide, 30 mm thick) clamped together, strip welded on the inside
- * 4 mm wear plates over full height and full length of the trailer
- * Top rail is reinforced with wood and steel, in order to better sustain rough loading conditions

Front bulkhead:

- * Straight and reinforced front bulkhead in smooth 600 mm panels- With large safety catwalk: width 360mm
- * 800 mm banister, with handhold and safety chain.
- * With ladder on both sides

Backdoor :

- * Smooth barn type backdoor.
- * With exchangeable rubber sealing
- * Closing by means of 2 scrap hooks (one on each door half) and pneumatic hook at the bottom
- * With steel header bar

ROOF CONSTRUCTION AND SHEET

- * 1 Raised fixed steel cross bar
- * Standard UK roll over sheet
- * Sheet operated at the front from the catwalk using T drive handle

FINISHING

- * Chemical cleaning of the alloy parts
- * Body hand polished, chassis and body primed with 2 paint coats and 2 top coats enamel paint, 2 color painting (free choice, with the exception of metallic finish)

FOR SALES CONTACT:

TC TRAILERS
 UNIT 4B, SANTRY HALL IND.EST.
 SANTRY, DUBLIN 9
 IRELAND
 TEL: 01 862 3474
 FAX: 01 862 3475
 Email: tctrailers@eircom.net



KONSTRUKTIEWERKHUIZEN

STAS NV

FLANDERS FIELDWEG, 45 - INDUSTRIEZONE E17

B-8790 WAREGEM

TEL. +32 56 600 191

FAX +32 56 600 195

WWW.STAS.BE / WWW.ALUTRAILER.COM

E-MAIL : SALES@STAS.BE

Version : UK - 24-03-2005



ECO EVO II